Email : sales@scilabexport.com
Phone: +91-7082934803

Product Name :

Precision Balance, 220g

Product Code :

SLE/LB/25



Email : sales@scilabexport.com
Phone: +91-7082934803

Description :

The Precision Balance, 220g reads to 0.001g across its 220g capacity, with a repeatability of 0.002g and a linearity of 0.003g. It prints results with the date andtime over USB or RS-232, has a sealed keypad and 24mm backlit digits, and iscalibrated externally with weights.

220 g milligram balance specifications

Parameter	Detail
Capacity	220g
Readability / repeatability / linearity	0.001g / 0.002g / 0.003g
Weighing pan	Grade 304 stainless steel, 120mm diameter
Display	Backlit LCD, 24mm white digits on a black background
Weighing units	mg, g, ct, GN, dr, ozt, dwt, mm, tl.T, tl.H, tl.S, T, custom unit
Calibration	External, with weights
Interfaces	USB and RS-232
Power supply	18V DC 50/60Hz 830mA adapter; AC adapter included
Housing and conditions	ABS plastic; 224 x 374 x 219mm (w x d x h); 4.1kg net; operating temperature 15° to 35°C
Product code	SLE/LB/25
Minimum order	10 units
Dispatch	Usually within 7 to 10 working days
Supplied by	ScienceLab (Jain Scientific Equipments Pvt Ltd), Ambala, India

Milligram practicals on the 220 g balance

Thickness of aluminium foil. Cut a square of kitchen foil, measure its sides with a metal ruler, fold it into a small pad and weigh it. Divide the mass by the density of aluminium and by the area of the square. The answer is the foil thickness, a small fraction of a millimetre.

Yield of copper sulfate crystals. Warm copper oxide with dilute sulfuric acid, filter off the excess and evaporate the blue solution in a porcelain dish until crystals start to form. Dry the crystals on filter paper, weigh them and compare the mass with the yield expected from the acid used, since the copper oxide was in excess.

Grow e and ing. Use b, and

Email : sales@scilabexport.com
Phone: +91-7082934803