

 ${\bf Email: sales@scilabexport.com}$ 

Phone: +91-7082934803

# **Product Name:**

**Product Code:** 

Precision Balance, 220g

SLE/LB/25





Email: sales@scilabexport.com

Phone: +91-7082934803

## **Description:**

With numerous features and functions, precision balances are suitable for most lab weighing tasks.

It's display features a stylish look, with easy-to-read 24mm digits in white on a black background. Ideal for international use, provides multilingual text and display capabilities.

USB and RS-232 interfaces facilitate data gathering and enable smooth communication with printers and computers.

The grade 304 stainless steel pan and sturdy ABS plastic construction are easy to keep clean, giving the rugged durability needed in a lab balance.

Display: Vivid, backlit LCD easily visible in any lighting conditions

Power: AC adapter included

#### Hardware:

Colour-coded keys facilitate quick recognition of the most frequently used buttons Security slot for optional Kensington-type lock and cable to help prevent theft Large, grade 304 stainless steel pan allows easy cleaning Sealed keypad protects against dirt and spills

Level indicator and adjustable feet ensure proper balance setup for optimum weighing results USB and RS-232 interfaces provide speedy communication with computers and printers

#### Software:

External calibration allows for verification and adjustment with weights

Hold function freezes the displayed weight, allowing time to elapse without losing the result Printouts include date and time for data tracking within Good Laboratory Practices (GLP) guidelines

Selectable digital filtering for animal/dynamic weighing enables consistent results for moving subjects

Multilingual display allows use in many different countries

Parts counting with preset sample sizes

Auto power-off to save energy

### **Technical Specifications:**

Capacity: 220g

Stabilisation Time: 2.0 Pan Size: 120mm ø

Weighing Units: mg, g, ct, GN, dr, ozt, dwt, mm, tl.T, tl.H, tl.S, T, custom unit

Calibration: External calibration

Power Supply: 18V DC 50/60Hz 830mA adapter

**Construction:** ABS plastic Interface: RS-232, USB

Linearity: 0.003g Readability: 0.001g Repeatability: 0.002g

Operating Temperature: 15° to 35°C

Net Weight: 4.1kg

Overall D Display [

Website: https://www.scilabexport.com, Email: sales@scilabexport.com

Contact S

1226/1-5. Bengali Mohalla, Science Market I 133001, Harvana



Email: sales@scilabexport.com

Phone: +91-7082934803